## ROOSTER LOOP S-03.02.30





| Flow Rate          | 10-14 gpm - 30-33 ipm                                     |  | Material Detail |         | Coating / Oraphic Design  |                |  |
|--------------------|---|--|-----------------|---------|---|----------------|--|
| Pressure<br>Height | 8-14 psi - 0.5-1 bar<br>108.6" - 276 cm                   | Commercial, non corrosive, chemical<br>resistant 304/304L quality stainless<br>steel and glass reinforced polyester<br>material with brass nozzles |                 |         | UV and chemical resistant, oven cured,<br>polyester powder coating.<br>UV and chemical resistant, commercial<br>grade epoxy coated spray paint. |                |  |
| Height             | 100.0 - 270 cm  |  |                 |         | Pipe Diameter   | ø3" - ø90 mm   |  |
| Length             | -   |  |                 |         | ripe Diameter   | 83 - 870 11111 |  |
|                    |   |  |                 |         | Add-in Options  |                |  |
| Width              | 74.8″ - 190 cm  | Play Zones   |                 |         |   |                |  |
| Spray Zone         | ø100" - ø254 cm   | Toddler  | Family          | Dynamic | Removable   |                |  |
| www.waterspla      |   |  | M 1487          |         |   |                |  |
| (800) 936-         | ASTM 1487<br>ASTM 2461<br>Standard Workfaule<br>ASTM 2461 |  |                 |         |   |                |  |